


A1009 501330 CONNECTOR

1.00mm Pitch/Disconnectable Crimp style connectors



Specifications:

- Current rating: 1.0 A AC,DC
- Voltage rating: 100 V AC/DC
- Temperature range: -25°C ~ +105°C
(including temperature rise in applying electrical current)
- Contact resistance: Initial value/ 30m Ω max
After environmental testing/ 40m Ω max
- Insulation resistance: 500 M Ω min
- Withstanding voltage: 500 VAC/minute
- Applicable wire: Conductor size/ AWG#32 to #28

- * Compliant with RoHS2/ REACH/ HF
- * In using the products, refer to "Handling Precautions for Terminals and Connectors" described on our website (Technical documents of Product information page).
- * Contact CSG for details

Material:


Housing: PA66,UL94-V0;Color:White

Terminal: Phosphor/ Tin-plated, Gold-Plated

Wafer Housing: LCP/ 4T/ 9T,UL94-V0;Color:Natural/ Black

Wafer Pin: Phosphor/ Tin-plated

Wafer Fixed Foot: Brass/ Tin-plated





- Note: 1. The above figure is the figure viewed from the connector mounting side.
2. Tolerances are non-cumulative: ± 0.08 mm for all centers.
3. The dimensions above should serve as a guideline. Contact CSG for details.

CSG





Tel: +86-769-85312070 85375507 E-mail: James@csg-china.com www.csg-china.com

A1009 501330



A1009HF 0XX AA P6 9 006
 PIN
 002=2PINS
 SPECIAL
 AA=NO Protrusions
 AK=BUCKLE
 Material
 P6=PA66 94V-0
 Code
 006
 Color
 9=White

CSG PART NO.	Dimension mm		Q'ty/BAG
	A	B	
A1009HF002AAP69006	1.00	3.70	1000PCS
A1009HF003AAP69006	2.00	4.70	1000PCS
A1009HF004AAP69006	3.00	5.70	1000PCS
A1009HF005AAP69006	4.00	6.70	1000PCS
A1009HF006AKP69006	5.00	7.70	1000PCS
A1009HF007AKP69006	6.00	8.70	1000PCS
A1009HF008AKP69006	7.00	9.70	1000PCS
A1009HF009AKP69006	8.00	10.70	1000PCS
A1009HF010AKP69006	9.00	11.70	1000PCS
A1009HF011AKP69006	10.00	12.70	1000PCS
A1009HF012AKP69006	11.00	13.70	1000PCS
A1009HF013AKP69006	12.00	14.70	1000PCS
A1009HF014AKP69006	13.00	15.70	1000PCS
A1009HF015AKP69006	14.00	16.70	1000PCS









A1009 M 0 A XX 006
 Type
 M=Female Terminal
 Material
 A=Phosphor
 Finish
 TP=Tin-Plated
 GF=Gold-Plated
 Code
 006

CSG PART NO.	Wire Range	Insulation O.D.	Q'ty/Reel
A1009M0ATP006	AWG#28-#32	0.75mm(max)	20000PCS
A1009M0AGF006	AWG#28-#32	0.75mm(max)	20000PCS







CSG

A1009 501330



A1009HF 0XX AA P6 9 079
PIN
002=2PINS
SPECIAL
AK=BUCKLE
Material
P6=PA66 94V-0
Code
079
Color
9=White

CSG PART NO.	Dimension mm		Q'ty/BAG
	A	B	
A1009HF003AKP69079	2.00	4.70	1000PCS
A1009HF004AKP69079	3.00	5.70	1000PCS
A1009HF005AKP69079	4.00	6.70	1000PCS








A1009HF 0XX AA P6 9 001
PIN
002=2PINS
SPECIAL
AK=BUCKLE
Material
P6=PA66 94V-0
Code
001
Color
9=White

CSG PART NO.	Dimension mm		Q'ty/BAG
	A	B	
A1009HF003AKP69001	2.00	4.70	1000PCS
A1009HF004AKP69001	3.00	5.70	1000PCS
A1009HF005AKP69001	4.00	6.70	1000PCS

CSG






A1009 501330



Recommended P.C.B Layout
General Tolerance±0.05

A1009RS.0XX AA LP TP B A 001
PIN
002=2PINS
SPECIAL
AA=NO Special
Material
LP=LCP 94V-0
Finish
TP=Terminal Tin-Plated
Code
001
Color
A=Natural
Packing
B=Tape & Reel

CSG PART NO.	Dimension mm		Q'ty/Reel
	A	B	
A1009RS002AALPTPBA001	1.00	4.00	1000PCS
A1009RS003AALPTPBA001	2.00	5.00	1000PCS
A1009RS004AALPTPBA001	3.00	6.00	1000PCS
A1009RS005AALPTPBA001	4.00	7.00	1000PCS






Recommended P.C.B Layout
General Tolerance±0.05

A1009RS.0XX AA 4T XX B A 001
PIN
002=2PINS
SPECIAL
AA=NO Special
Material
4T=PA4T 94V-0
Finish
TP=Terminal Tin-Plated
GF=Terminal Gold-Plated
Code
001
Color
A=Natural
Packing
B=Tape & Reel


CSG PART NO.	Dimension mm		Q'ty/Reel
	A	B	
A1009RS006AA4TXXBA001	5.00	8.00	1000PCS
A1009RS007AA4TXXBA001	6.00	9.00	1000PCS
A1009RS008AA4TXXBA001	7.00	10.00	1000PCS
A1009RS009AA4TXXBA001	8.00	11.00	1000PCS
A1009RS010AA4TXXBA001	9.00	12.00	1000PCS
A1009RS011AA4TXXBA001	10.00	13.00	1000PCS
A1009RS012AA4TXXBA001	11.00	14.00	1000PCS
A1009RS013AA4TXXBA001	12.00	15.00	1000PCS
A1009RS014AA4TXXBA001	13.00	16.00	1000PCS
A1009RS015AA4TXXBA001	14.00	17.00	1000PCS

CSG


A1009 501330






Recommended P.C.B Layout
General Tolerance±0.05



A1009VS002AAALPTPBA001
PIN
002=2PINS
SPECIAL
AA=NO Special
Material
LP=LCP 94V-0
Finish
TP=Terminal Tin-Plated
Code
001
Color
A=Natural
Packing
B=Tape & Reel






CSG PART NO.	Dimension mm		Q'ty/Reel
	A	B	
A1009VS002AALPTPBA001	1.00	4.00	800PCS
A1009VS003AALPTPBA001	2.00	5.00	800PCS
A1009VS004AALPTPBA001	3.00	6.00	800PCS
A1009VS005AALPTPBA001	4.00	7.00	800PCS



Recommended P.C.B Layout
General Tolerance±0.05


A1009VS006AA4TXXBA001
PIN
002=2PINS
SPECIAL
AA=NO Special
Material
4T=PA4T 94V-0
Finish
TP=Terminal Tin-Plated
GF=Terminal Gold-Plated
Code
001
Color
A=Natural
Packing
B=Tape & Reel






CSG PART NO.	Dimension mm		Q'ty/Reel
	A	B	
A1009VS006AA4TXXBA001	5.00	8.00	800PCS
A1009VS007AA4TXXBA001	6.00	9.00	800PCS
A1009VS008AA4TXXBA001	7.00	10.00	800PCS
A1009VS009AA4TXXBA001	8.00	11.00	800PCS
A1009VS010AA4TXXBA001	9.00	12.00	800PCS
A1009VS011AA4TXXBA001	10.00	13.00	800PCS
A1009VS012AALPTPBA001	11.00	14.00	800PCS
A1009VS013AA4TXXBA001	12.00	15.00	800PCS
A1009VS014AA4TXXBA001	13.00	16.00	800PCS
A1009VS015AA4TXXBA001	14.00	17.00	800PCS

CSG






A1009 501330



A1009HF 2XX AK P6 9 001
 PIN 210=2X10PINS
 SPECIAL
 AK=BUCKLE
 Material P6=PA66 94V-0
 Code 001
 Color 9=White



CSG PART NO.	Dimension mm		Q'ty/BAG
	A	B	
A1009HF210AKP69001	9.00	11.70	1000PCS
A1009HF215AKP69001	14.00	16.70	1000PCS
A1009HF220AKP69001	19.00	21.70	1000PCS
A1009HF225AKP69001	24.00	26.70	1000PCS






Recommended P.C.B Layout
 General Tolerance±0.05

A1009RS 2XX AA 4T XX B X 001
 PIN 210=2X10PINS
 SPECIAL
 AA=NO Special
 Material 4T=PA4T 94V-0
 Finish GF=Terminal Gold-Plated
 TP=Terminal Tin-Plated
 Code 001
 Color A=Natural
 0=Black
 Packing B=Tape & Reel



CSG PART NO.	Dimension mm		Q'ty/BAG
	A	B	
A1009RS210AA4TXXBX001	9.00	12.30	400PCS
A1009RS215AA4TXXBX001	14.00	17.30	400PCS
A1009RS220AA4TXXBX001	19.00	22.30	400PCS
A1009RS215AA4TXXBX001	24.00	27.30	400PCS

CSG

A1009 501330



Recommended P.C.B Layout
General Tolerance±0.05



A1009VS 2XX AA 9T GF B A 112
PIN
210=2X10PINS
SPECIAL
AA=NO Special
Material
9T=PA9T 94V-0
Finish
GF=Terminal Gold-Plated
Code
112
Color
A=Natural
Packing
B=Tape & Reel

CSG PART NO.	Dimension mm		Q'ty/BAG
	A	B	
A1009VS210AA9TGFB A112	9.00	12.30	800PCS
A1009VS215AA9TGFB A112	14.00	17.30	800PCS
A1009VS220AA9TGFB A112	19.00	22.30	800PCS
A1009VS225AA9TGFB A112	24.00	27.30	800PCS

CSG