产品规格书 PRODUCT SPECIFICATION

工程变更记录

版本号	变更日期	变更描述

产品规格书 PRODUCT SPECIFICATION

1. 适用范围 SCOPE

本规范适用于 P/F1000 系列条形连接器，包含了产品的性能、试验方法和检验要求。
This specification applies to P/F1000 bar connector series, contains the product performance, test
methods and inspection requirements.

2. 适用的标准 APPLICABLE STANDARDS

2.1 GB/T2421 电工电子产品环境试验 第一部分 总则
Testing method for Environmental of Electrical Connectors
Class 1: general Principles

2.2 GB/T2423 电工电子产品环境试验方法
Testing method for Environmental of Electrical Connectors

2.3 GB/T2424 电工电子产品环境试验导则
Testing method for Environment of Electrical Connectors

2.4 GB/T5095 电子设备用机电元件基本试验规程及测量方法
Testing Procedure/method for Components of Electrical Equipment

3. 外观及尺寸 APPEARANCE AND DIMENSION

3.1 外观 appearance

经目视观察，外观不可有变形，电镀脱落等会降低其功能的异常现象，也不可有严重破裂、刮伤或污损之缺点。
By looking, there shall not be any abnormality such as deformity, exfoliation of plating, etc., which can reduce performance. No defect such as cracks scratches or blemishes.

3.2 尺寸 measure

参照工程图
With reference to engineering drawing

3.3 互换性 interchangeability

互换性：相同规格应能互换
Exchangeable: Exchangeable with same specification products

3.4 建议 PCB LAYOUT 图 Recommended PCB LAYOUT drawing

参照工程图
With reference to engineering drawing

产品规格书 PRODUCT SPECIFICATION

4. 材质 THE MATERIAL

P/N(零件名称)	TYPE(类型)	Material(材料)	Finish(表面处理)	Explain(说明)
P/F1000VD P/F1000RD P/F1000VS	Plastic (塑胶)	PA6T/ PBT/ LCP/ PA66(94V-0) 黑色/ Black		RoHS Compliant
	Termainal:(端子)	Phosphor bronze(磷青铜)	Gold-plating(镀金) /Tin-plating镀锡	
	Contact (PIN 针)	Bass(黄铜) / Phosphor bronze(磷青铜)		

5. 标准额定值 RATINGS

项 目 ITEM	规 格 SPECIFICATIONS
额 定 电 压 Rated Voltage	50V
额 定 电 流 Rated current	0.75A AC /DC
温 度 范 围 Temperature Range	－40℃ ～ ＋105℃
湿 度 范 围 Humidty range	相对湿度 65％以下 Relative humidity 65％ max
保存温度范围 Storage temperature range	－10℃ ～ ＋50℃
保存湿度范围 Storage humidity range	相对湿度 65％以下 Relative humidity 65％ max

6. 部件名称&部件编号 Part name & part number

部 件 名 称 Part name	部 件 编 号 Part number
Housing	
Terminal	
Wafer (DIP)	P/F1000VD P/F1000RD
Wafer (SMT)	P/F1000VS

产品规格书 PRODUCT SPECIFICATION

7.电气特性 ELECTRICAL EFFICIENCY

No.编号	项目 Item	试验方法 Test Method	性能要求 Requirement
7.1	接触电阻 Contact Resistance	测量时将连接器插合，两端施以最大测试电压 20mV 以及最大测试电流 100mA ，测量时减去导线电阻值。Mate connectors, load voltage: A maximum voltage of 20mV and a maximum current of 100mA are applied to the Mate connector.	20mΩ Max.
7.2	绝缘电阻 Insulation Resistance	相邻接触体1 分钟时间内施加500V DC 电压进行测试测量期间的绝缘阻抗值。Mate connectors, Apply 500V DC(rms) for 1minute between adjacent contacts to measure the insulation resistance.	1000MΩ Min.
7.3	耐电压 Withstanding Voltage	在各相邻接触件间施加 500V AC 之电压持续 1 分钟。Mate connectors, apply 500V AC for 1 minute Between adjacent terminal or ground.	无击穿或者产生火花 No breakdown or flashover

8.环境特性 ENVIRONMENTAL EFFICIENCY

No.[编号]	项目 Item	试验方法 Test Method	性能要求 Requirement	
8.1	耐热试验 Heat Resistance	将连接器放在温度为+105±2℃的环境中 96 小时，再置于室温下 1～2 小时。Mated connector shall be placed in an environmental for 96 hours at +105±2℃, Again in 1 ~ 2 hours at room temperature .	外观 Appearance	目视外观无任何损坏异状 No Breakdown
			接触阻抗 Contact Resistance	20mΩ Max.
8.2	耐冷试验 Cold Resistance	将连接器放在温度为-25±3℃的环境中 96 小时，再置于室温下 1～2 小时。Mated connector shall be placed in an environmental for 96 hours at -25±3℃ Again in 1 ~ 2 hours at room temperature.	外观 Appearance	目视外观无任何损坏异状 No Breakdown
			接触阻抗 Contact Resistance	20mΩ Max.
8.3	耐湿性试验 Humidity	把插合的连接器，温度 40±2℃，相对湿度 60～65%的环境中，持续 96 小时。经试验后，连接器须于室	外观 Appearance	目视外观无任何损坏异状 No Breakdown

产品规格书 PRODUCT SPECIFICATION

		温中放置 1～2 小时，再测定其值。 Mate connectors,40 ± 2 ℃ in temperature and 60 ～ 65%RH in an environmental for 96 hours. After testing connector shall be left alone for 1 to 2 hours in a room ambient.	绝缘电阻 Insulation Resistance	1000MΩ MIN.
			耐电压 Withstanding Voltage	500V AC/minute MIN
8.4	温度循环 Temperature Cycling	低温:-25±3℃，30 分钟，放置转换时 10-15 分钟 高温:+105±3℃，30 分钟，放置转换时 10-15 分钟 5 次循环后放置在正常环境中恢复 2 小时后进行测试. Low temperature:-25±3℃,30min,room temp10-15min high temperature:+105±3℃,30min,room temp10-15min After 5 cycles at the normal environment for testing after 2 hours.	外观 Appearance	目视外观无任何损坏异状 No Breakdown
			接触电阻 Contact Resistance	20mΩ Max.
8.5	盐雾试验 Salt spray	盐水比重：5±1% 温度：35±2℃ 试验时间：24 小时，试验结束后用清水将残留盐份清洗并将水滴清除后，才可测量。 Salt concentration: 5±1%Temperature: 35±2℃ Testing time:24 hours, After salt is removed by running water and a drop is removed, it is measured.	外观 Appearance	镀层无剥落，无分离,无裂痕起皱,表面的腐蚀面积小于5% No peeling, no separation, no cracking and wrinkling of the coating, the surface corrosion area is less than 5%
			接触电阻 Contact Resistance	20mΩ Max.

产品规格书 PRODUCT SPECIFICATION

8.6	Solderability [可焊性试验]	焊锡时间：2.5±0.5 秒 焊锡温度：245±5℃(GB/T5095.6-12a) Soldering time: 2.5±0.5 S Solder Temperature: 245±5℃(GB/T5095.6-12a)	焊锡面积≥95% 95% min. of solder area
8.7	耐焊性 Resistance to soldering heat	将连接器置于 PCB 板上，然后将露出 PCB 板表面的 Pin 脚部分浸入 260 ℃±5 ℃ 的锡炉中 5 ±1 秒。(GB/T5095.6-12a) Place the connector on the P.C.Board, then immerse the solder pin up to the surface of the board in the solder bath at 260℃±5℃ for 5 ±1S .(GB/T5095.6-12a)	塑胶不得有明显的变形或损坏。 1.Without deformation of ease or excessive losses. 电气特性必须符合规格 2.Electrical characteristics shall be satisfied.

9.机械特性 MECHANICAL EFFICIENCY

No.[编号]	项目 Item	试验方法 Test Method	性能要求 Requirement	
9.1	PIN 针固定力Pin retention force	在针脚前端施加力，以每分钟 25±3mm 的速率，直到针退出针座的拔出力 Exerts a force on the pin end,at a rate per minute 25±3mm,until the needle exit seat pull-out force	单一PIN 5N Min.Only per PIN	
9.2	端子与孔座固定力 Terminal crimping wire stength	端子与孔座配合，以每分钟 25±3mm 的速率沿导线方向将端子从孔座中拔出的力。 The terminal and hole seat,at a rate per minute to 25±3mm along the wire direction are pulled out from the hole in the seat capacity		
9.3	机械寿命 Mechanical Life	1、连接器必须承受 50 次的插拔循环 2、测试速度：100mm/分钟 1、Connectors shall be subjected to 50 cycle of Insertion and Withdrawal. 2、Speed:100mm/minute	接触电阻 Contact Resistance	1000MΩ Max.

产品规格书 PRODUCT SPECIFICATION

9.4	插入力&拔出力 Insertion force (I.F.)& Withdrawal force (W.F.)	（1）试验方法 Test method：将孔座和端子配合好,与针座在同一轴线上进行插拔测试。(测试速度：20±5 mm/minute)。 Housing with crimped terminal and wafer shall be mated and unmated on the same axis. For the measurement of single circuit。(Speed:20±5mm/minute) （2）性能要求 Requirement：(UNITS: N)

Number of circuits	At initial		Number of circuits	At initial	
	I.F.(max)	W.F.(min)		I.F.(max)	W.F.(min)